

action series

La Serie Action hereda la excepcional calidad de sonido y la sólida construcción que han hecho de los sistemas profesionales D.A.S. un estándar internacional en el refuerzo de sonido. Diseñado a partir de la experiencia del "mundo real", ofrece a los usuarios un rendimiento extraordinario, una absoluta fiabilidad y una facilidad de uso sin precedentes. Ya sea en una instalación de alto nivel o sobre el escenario de un gran evento, la serie Action le proporcionará la potencia y definición necesarias para que su trabajo sea un éxito.



The Action series inherits the exceptional sound quality and rugged build that have made D.A.S. professional systems an international sound reinforcement standard. Designed from "real-world" experience, they offer users outstanding performance, absolute reliability, and unparalleled convenience. Whether it is in a high-profile venue or on the stage of a major event, the Action series will provide the power and definition needed to make your performance a success.

action series

action 8A

action 12A

action M12A



	MODEL	action 8A	action 12A	action M12A
Power Amplifier		720 Wpeak 360 Wcontinuous (Class D Bi-amplified)	1000 Wpeak 500 Wcontinuous (Class D Bi-amplified)	1000 Wpeak 500 Wcontinuous (Class D Bi-amplified)
Input Type		Balanced Differential Line	Balanced Differential Line	Balanced Differential Line
Input Impedance		Line: 20 kohms Mic: 20 kohms	Line: 20 kohms Mic: 20 kohms	Line: 20 kohms Mic: 20 kohms
Sensitivity		Line: 1.95 V (+8 dBu) Mic: 20 mV (-32 dBu)	Line: 1.95 V (+8 dBu) Mic: 20 mV (-32 dBu)	Line: 1.95 V (+8 dBu) Mic: 20 mV (-32 dBu)
Frequency Range (-10 dB)		60 Hz - 20 kHz	50 Hz - 20 kHz	60 Hz - 20 kHz
HF Horn Coverage Angles (-6 dB)		80° x 80°	80° x 50° (Rotatable)	80° x 50° (Rotatable)
Maximum Peak SPL at 1 m		120 dB	131 dB	130 dB
Transducers/Replacement Parts		LF: 8B4/8B4 HF: M-26/GM M-26	LF: 12Mi/GM 12Mi HF: M-34/GM M-34	LF: 12Mi/GM 12Mi HF: M-34/GM M-34
Enclosure Material		Birch Plywood	Birch Plywood	Birch Plywood
Color/Finish		Black/ISO-flex Paint	Black/ISO-flex Paint	Black/ISO-flex Paint
Connectors		INPUT: Female XLR LOOP THRU: Male XLR AC INPUT: powerCON	INPUT: Female XLR LOOP THRU: Male XLR AC INPUT: powerCON	INPUT: Female XLR LOOP THRU: Male XLR AC INPUT: powerCON
AC Power Requirements		115 V, 1.2 A, 50 Hz/60 Hz 230 V, 0.6 A, 50 Hz/60 Hz	115 V, 2.4 A, 50 Hz/60 Hz 230 V, 1.2 A, 50 Hz/60 Hz	115 V, 2.4 A, 50 Hz/60 Hz 230 V, 1.2 A, 50 Hz/60 Hz
Dimensions (H x W x D)		47.5 x 27.9 x 25.5 cm 18.7 x 11 x 10 in	65.3 x 37.8 x 32.4 cm 25.7 x 14.9 x 12.8 in	42 x 64.5 x 31.6 cm 16.6 x 25.4 x 12.5 in
Weight		9.9 kg (21.8 lb)	20 kg (44 lb)	19 kg (41.8 lb)
Accessories		AXU-AC8 U Bracket AXW-1 Wall Mount TRD-2 Speaker Stand TRD-6 Pole Mount	ANL-2 Eye Bolt AXU-RF12 U Bracket FUN-ACT-12 TRD-2 Speaker Stand TRD-6 Pole Mount	FUN-ACT-M12 Cover TRD-2 Speaker Stand TRD-6 Pole Mount

action 8

action 12

action M12

	MODEL	action 8	action 12	action M12
Peak Power Handling		600 W	1200 W	1200 W
RMS (Average) Power Handling ⁽¹⁾		150 W	300 W	300 W
Frequency Range (-10 dB)		60 Hz - 20 kHz	50 Hz - 20 kHz	63 Hz - 20 kHz
Nominal Impedance		8 ohms	8 ohms	8 ohms
On-axis Sensitivity 1 W/ 1 m		92 dB SPL	96 dB SPL	95 dB SPL
Maximum Peak SPL at 1 m		120 dB	131 dB	130 dB
HF Horn Coverage Angles (-6 dB)		80° x 80°	80° x 50° (Rotatable)	80° x 50° (Rotatable)
Enclosure Material		Birch Plywood	Birch Plywood	Birch Plywood
Color/Finish		Black/ISO-flex Paint	Black/ISO-flex Paint	Black/ISO-flex Paint
Transducers/Replacement Parts		LF: 8B/8B HF: M-26/GM M-26	LF: 12Mi/GM 12Mi HF: M-34/GM M-34	LF: 12Mi/GM 12Mi HF: M-34/GM M-34
Connectors		2 x NL4 Speakon	2 x NL4 Speakon	2 x NL4 Speakon
Dimensions (H x W x D)		47.5 x 27.9 x 25.5 cm 18.7 x 11 x 10 in	65.3 x 37.8 x 32.4 cm 25.7 x 14.9 x 12.8 in	42 x 64.5 x 31.6 cm 16.6 x 25.4 x 12.5 in
Weight		8.4 kg (18.5 lb)	18.5 kg (40.7 lb)	17.5 kg (38.5 lb)
Accessories		AXW-1 Wall Mount TRD-2 Speaker Stand TRD-6 Pole Mount	ANL-2 Eye Bolt AXU-RF12 U Bracket FUN-ACT-12 TRD-2 Speaker Stand TRD-6 Pole Mount	FUN-ACT-M12 Cover TRD-2 Speaker Stand TRD-6 Pole Mount

action 15A



action 215A



action 18A



action 218A



action 15A

1000 Wpeak
 500 Wcontinuous
 (Class D Bi-amplified)
 Balanced Differential Line
 Line: 20 kohms
 Mic: 20 kohms
 Line: 1.95 V (+8 dBu)
 Mic: 20 mV (-32 dBu)
 45 Hz - 20 kHz
 80° x 50° (Rotatable)
 131 dB
 LF: 15Mi/GM 15Mi
 HF: M-34/GM M-34
 Birch Plywood
 Black/ISO-flex Paint
 INPUT: Female XLR
 LOOP THRU: Male XLR
 AC INPUT: powerCON

115 V, 3 A, 50 Hz/60 Hz
 230 V, 1.5 A, 50 Hz/60 Hz
 77.4 x 44.6 x 43.6 cm
 30.5 x 17.6 x 17.2 in
 26 kg (57.2 lb)
 ANL-2 Eye Bolt
 FUN-ACT-15 Cover
 TRD-2 Speaker Stand
 TRD-6 Pole Mount

action 215A

1000 Wpeak
 500 Wcontinuous
 (Class D Bi-amplified)
 Balanced Differential Line
 Line: 20 kohms
 Mic: 20 kohms
 Line: 1.95 V (+8 dBu)
 Mic: 20 mV (-32 dBu)
 45 Hz - 20 kHz
 80° x 50° (Rotatable)
 134 dB
 LF: 2x15Mi4/GM 15Mi4
 HF: M-44/GM M-44
 Birch Plywood
 Black/ISO-flex Paint
 INPUT: Female XLR
 LOOP THRU: Male XLR
 AC INPUT: powerCON

115 V, 3.6 A, 50 Hz/60 Hz
 230 V, 1.8 A, 50 Hz/60 Hz
 115.4 x 44.7 x 47.4 cm
 45.5 x 17.6 x 18.7 in
 40 kg (88 lb)
 ANL-2 Eye Bolt
 FUN-ACT-215 Cover

action 18A

1500 Wpeak
 750 Wcontinuous
 (Class D)
 Balanced Differential Line
 Line: 20 kohms
 Line: 1.95 V (+8 dBu)
 35 Hz -160 Hz (variable LPF)

 133 dB
 LF: 18H/GM 18G
 Birch Plywood
 Black/ISO-flex Paint
 INPUT: 2 x Female XLR
 LOOP THRU: 2 x Male XLR
 AC INPUT: powerCON

115 V, 3 A, 50 Hz/60 Hz
 230 V, 1.5 A, 50 Hz/60 Hz
 62.4 x 54 x 65 cm
 24.6 x 21.3 x 25.6 in
 36.5 kg (80.3 lb)
 FUN-ACT-18 Cover
 TRD-6 Pole Mount

action 218A

2500 Wpeak
 1250 Wcontinuous
 (Class D)
 Balanced Differential Line
 Line: 20 kohms
 Line: 1.95 V (+8 dBu)
 35 Hz - 160 Hz (variable LPF)

 139 dB
 LF: 2 x 18H4/GM 18H4
 Birch Plywood
 Black/ISO-flex Paint
 INPUT: 2 x Female XLR
 LOOP THRU: 2 x Male XLR
 AC INPUT: powerCON
 AC OUTPUT: powerCON

115 V, 5.4 A, 50 Hz/60 Hz
 230 V, 2.7 A, 50 Hz/60 Hz
 106.7 x 54 x 67 cm
 42 x 21.3 x 26.4 in
 63 kg (138.6 lb)
 FUN-ACT-218 Cover
 TRD-6 Pole Mount

action 15

action 15

1400 W
 350 W
 47 Hz - 20 kHz
 8 ohms
 96 dB SPL
 131 dB
 80° x 50° (Rotatable)
 Birch Plywood
 Black/ISO-flex Paint
 LF: 15Mi/GM 15Mi
 HF: M-34/GM M-34
 2 x NL4 Speakon
 77.4 x 44.6 x 43.6 cm
 30.5 x 17.6 x 17.2 in
 24.5 kg (53.9 lb)
 ANL-2 Eye Bolt
 FUN-ACT-15 Cover
 TRD-2 Speaker Stand
 TRD-6 Pole Mount

action 215

action 215

2800 W
 700 W
 47 Hz - 20 kHz
 4 ohms
 99 dB SPL
 134 dB
 80° x 50° (Rotatable)
 Birch Plywood
 Black/ISO-flex Paint
 LF: 2x15Mi/GM 15Mi
 HF: M-44/GM M-44
 2 x NL4 Speakon
 115.4 x 44.7 x 47.4 cm
 45.5 x 17.6 x 18.7 in
 38.5 kg (83.6 lb)
 ANL-2 Eye Bolt
 FUN-ACT-215 Cover

action 18

action 18

2400 W
 600 W
 33 Hz - 160 Hz
 8 ohms
 96 dB SPL
 133 dB

 Birch Plywood
 Black/ISO-flex Paint
 LF: 18H/GM 18G
 2 x NL4 Speakon
 62.4 x 54 x 65 cm
 24.6 x 21.3 x 25.6 in
 34.5 kg (75.9 lb)
 FUN-ACT-18 Cover
 TRD-6 Pole Mount

action 218

action 218

4800 W
 1200 W
 29 Hz - 160 Hz
 4 ohms
 99 dB SPL
 139 dB

 Birch Plywood
 Black/ISO-flex Paint
 LF: 2 x 18H/GM 18G
 2 x NL4 Speakon
 106.7 x 54 x 67 cm
 42 x 21.3 x 26.4 in
 61 kg (134.2 lb)
 FUN-ACT-218 Cover
 TRD-6 Pole Mount