



CL-8-T



DESCRIPTION

The CL-8T is a 2-way passive full-range ceiling loudspeaker that incorporates an 8" cone low frequency transducer and a ferrofluid cooled 1" soft dome high frequency unit with integral diffraction-ring. The unit is equipped with a multitap line transformer. The system's low frequency driver is mounted on a plastic support with mounting tabs for fixing to ceiling surfaces. The front of the system is protected by a perforated metal grille.

KEY FEATURES

- 8" ceiling mount loudspeaker
- 50 Hz - 20 kHz bandwidth
- Multi-tap 70V/100V transformer
- Easy mounting system with built-in tabs

APPLICATIONS

- Professional Installation Systems
- Houses of Worship
- Auditoriums/Theaters
- Hotel Ballrooms and Meeting Rooms

SPECIFICATIONS

Performance

Frequency Range (-10 dB)	50 Hz - 20 kHz
Horizontal Coverage (-6 dB)	90°
Nominal Impedance	8 ohms
Transformer Taps 70 V	Tap1, 5 W. Tap2, 7.5 W. Tap3 10 W.
Transformer Taps 100 V	Tap1, 10 W. Tap2, 20 W. Tap3 30 W.
On-axis Sensitivity 1W/1 m	90 dB SPL
Recommended Amplifier	IA-402 IA-404

Connectors

Audio Input Connector	Spring Terminals
Audio Output Connector	Spring Terminals

Enclosure

Enclosure Geometry	Round
Color	White
Cut Out Diameter	242 mm (9,5 in)
Depth	97 mm (3,8 in)
Net Weight	1,8 kg (4,0 lb)

Shipping

Carton Dimensions (H x W x D)	310 x 300 x 450 mm 12,2 x 11,8 x 17,7 in
Shipping Weight	2,1 kg (4,6 lb)



ORDERING INFORMATION

Performance

Model	Description	P/N
-------	-------------	-----

System

CL-8-T	2-way Passive Co-axial	10213060
--------	------------------------	----------

DIMENSIONS

