

DIMENSIONS





CHANNELS

CH1	Pan	
CH2	Tit	Ø : 285'
CH3	Speed	
CH4	Shutter Function	Normal Of Pulse Of Random
CH5	Shutter	Open Of Slow Off Fast
CH6	Dimmer	0 • 255
CH7	Color Function	🕒 🖲 🕘 🥌 Slow 🎒 Fast
CH8	Color	$\bigcirc \bullet \bullet$
CH9	Ret Gobo Function	°0, • © © •
CH10	Ret Gobo	$(\textcircled{O}) \circ \longrightarrow 250 (\textcircled{O}) \circ \longrightarrow 255$
CH11	GeboRet Function	🗳 🎯 🍥 🗳
CH12	Gobo Rot	(a) 0 → 210 (a)
CH13	Gobo Function	
CH14	Fixed Gobo	1-15 🏶 🛞 🔘 •> 250
CH15	Prism	0 🛛 🏶 🔍
CH16	Prism Rot	$\bigcirc \longrightarrow 127 \bigcirc 123 \longrightarrow 255$
CH17	Focus	
CH18	Focus Function	0 🖉 255 (5-7.5-10-15-20)m
CH19	Zoom	$\circ \rightarrow \circ$
CH20	Control	(Pan&Til, Color, Sobo, Other) Reset All Display office Hibernation





The CL 390 SBW is a hybrid beam/spot/wash 3 in 1 model with super-short-arc lamp for the best brightness. The multi functions make this model suitable for all kinds of applications. Functions include color wheel, notating gabo wheel plus one more static gabo wheel, effect wheel with 4 linear+81 circular prism and frost, focus, fast zoom from 2 to 23 degree.

SPECIFICATIONS

Luminous Flux: 12000lumen, 620000lux@5m@2º beam mode, 31390lux@5m@5.5º spot mode Control: Remote on/off via DMX Ballast: switching mode power supply Beam anale: 2º-10º beam.5.5º-23º spot Pan: 630° (4.0 sec) or 540° (3.58 sec). Tilt: 265° (2.8 sec) 16-bit resolution Auto repositioning Colors 13+open, interchangeable, indexable and bidirectional rainbow effect Color bounce Rotating gobo wheel: 9 (glass)+open Static gobo wheel, 14+open Real indexable and aobo shaking Distinctive gobo animation effect DMX channels: 20/24/14/16 Color wheel: 13+1 colors Rotating gobo wheel: 9+1 gobos Static gobo wheel: 14+1 gobos Zoom: 2.10. beam, 5.5.-23. spot Motorized focus Full range 0-100% dimmer Various strobe Frost 6-linear+8facets prism RDM function to change DMX address, display flip, X/Y Reverse and so on RDM read voltage, current, power consumption of lamp Software upgrade via DMX Hibernation when lost DMX for preset time Indicate temperature into of base, arm and lamp Fan speed auto change according to temperature 2.4inch super nice LCD display with friendly English/ Chinese/French/Spanish menu Auto look Rin Back-up communicating IC Power Max power consumption: 430W Powercon in and out Power supply: Electronic auto-ranging Input voltage range: 100-240V, 50-60Hz Fixture: 369X402X623MM Packina: 720X430X350MM Net Weight: 17KG Gross Weight: 19KG Mounting points: 4 1/4-turn locks 2 x Omega brackets with 1/4-turn quick locks Safety rope