



a new
concept of
high power
lighting

. the
light
side
of the
moon

Studio Due
emotion and creativity in light



Envision the future.

Creating memorable lighting experiences for a bright future.


High power LED lighting solutions from Studio Due help you to realise your creative ambitions with precision and accuracy beam spread.

Designed to provide the highest levels of energy efficient light output and to replace traditional luminaires at cost effective prices.

Manufactured using high quality materials and components aiming to minimise the environmental impact and reduce maintenance costs.



Studio Due.
emotion and creativity in **light**.



Headquarter: STUDIO DUE light s.r.l.
Str. Poggino, 100 - 01100 Viterbo (Italy)
tel. +39.0761.352520 (4 lines)
fax +39.0761.352653

STUDIO DUE UK
3 Encon Court, Owl Close
Moulton Park Industrial Estate
Northampton (England) UK - NN3 6 HZ
tel. +44.1933.650.820

STUDIO DUE Far East LTD
Unit 8, 4/F, Harbour Centre Tower II, 8 Hok Cheung St,
Hung Hom, Kowloon (Hong Kong)
tel. +852.29542141 fax +852.23302515


www.studiodue.com

emotion and creativity in **light**

. the
light
side
of the
moon

new Citycolor LED rgb/full color



- Same light output of traditional CityColor
- 1/3 of its power consumption
- 1/3 of its weight
- Up to 65° wide beam angle
- Small and lightweight



Light source	n. 168 RGB 3W led
Total led power	504W
Standard optic	25° (12.5+12.5) 26 mm lenses
Available on request	40° (20+20) 26 mm lenses
Available as accessory	<ul style="list-style-type: none"> • 65° plan-filter • Barn-door • Anti-glare
Head tilt	Manual 240°
Adjustable light blocks	2 adjustable light blocks +9° each
Control	Standard interface: RS-485, optocoupled input Protocol: USITT DMX512
Connections	Signal: 4pin IP 67 connector (male-female) Main Power: 3x1mm cable
Available as accessory	<ul style="list-style-type: none"> • XLR 3/5pin+Powercon in-out box • Wireless DMX receiver
Safety	n. 4 eyebolts for safety chains
DMX channels	9CH mode - 5CH mode - 4CH mode
Setup and configuration	Control panel with touch technology Led display with flip function Dedicated DMX channel for white balance DMX or Auto mode with Master-Slave function Intelligent temperature control Flicker-free function Smooth dimming function Halogen simulation CYM simulation
Rating protection	IP 64
Power supply	2x320W switching power supply Rated voltage 100-240V~ Frequency 50-60Hz Rated current 2.5A@230V-Fuse T10A Active PFC Power consumption 560W (all color full power)
Physical	WxDxH: 690x150x610 mm Weight: 32 Kg.



CitycolorLED

art. 1302 Citycolor led rgb/fc



The Citycolor LED with the optional art. **CCLED-FRH** (frame holder) + the optional art. **CCLED-AG** 2 pcs. (anti glare) mounted.



The optional art. **CCLED-FRH** (frame holder) + optional art. **CCLED-BD** 4 pcs. (barn door with extension) to define the illuminated surface.



The optional art. **CCLED-FRH** (frame holder) + optional art. **CCLED-BD** 4 pcs. (barn door with extension) + the optional art. **CCLED-AG** 2 pcs. (anti glare) mounted.

Art. **CCLED-AD BOX**, is the optional XRL + Powercon adapter box (IP20).



Art. **CCLED-FROST**. Optional kit wide beam (2 pcs.) to increase the light beam up to 65°.



new
CitybeamLED24 rgbw/full color

- Astonishing level of brightness up to 250 meters
- High Power 12W RGBW LEDs
- 5° very narrow beam
- Energy efficient



Light source n. 24 RGBW 12W led
 Total led power 288W
 Standard optic 5° (2.5+2.5) 45 mm lenses
 Available on request Medium, wide 45 mm lenses

Tilt Manual 160°

Control Standard interface: RS-485, optocoupled input
 Protocol: USITT DMX512.

Connections Signal: 4pin IP 67 connector (male-female)
 Main Power: 3x1mm cable
 Available as accessory • Wireless DMX receiver

Safety n. 2 eyebolts for safety chains

DMX channels 9CH mode - 5CH mode - 4CH mode

Setup and configuration Control panel with touch technology
 Led display with flip function
 Dedicated DMX channel for white balance
 DMX or Auto mode with Master-Slave function
 Intelligent temperature control
 Flicker-free function
 Smooth dimming function
 Halogen simulation
 CYM simulation

Rating protection IP 66

Power supply 320W switching power supply
 Rated voltage 100-240V~
 Frequency 50-60Hz
 Rated current 1.1A@230V-Fuse T5A
 Active PFC
 Power consumption 250
 (all color full power)

Physical WxDxH: 615x180x420
 Weight: 18,5

CitybeamLED²⁴
RGBW full color

art. 1304 Citybeam led 24 rgbw/fc

new
CitybeamLED12 rgbw/full color



Light source n. 12 RGBW 12W led
 Total led power 144W
 Standard optic 5° (2.5+2.5) 45 mm lenses
 Available on request Medium, wide 45 mm lenses

Tilt Manual 160°

Control Standard interface: RS-485, optocoupled input
 Protocol: USITT DMX512.

Connections Signal: 4pin IP 67 connector (male-female)
 Main Power: 3x1mm cable

Available as accessory • Wireless DMX receiver

Safety n. 2 eyebolts for safety chains

DMX channels 9CH mode - 5CH mode - 4CH mode

Setup and configuration Control panel with touch technology
 Led display with flip function
 Dedicated DMX channel for white balance
 DMX or Auto mode with Master-Slave function
 Intelligent temperature control
 Flicker-free function
 Smooth dimming function
 Halogen simulation
 CYM simulation

Rating protection IP 66

Power supply 320W switching power supply
 Rated voltage 100-240V~
 Frequency 50-60Hz
 Rated current 0,6A@230V-Fuse T5A
 Active PFC
 Power consumption 130W
 (all color full power)

Physical WxDxH: 355x180x420
 Weight: 12Kg.

CitybeamLED¹²

art. 1303 Citybeam led 12 rgbw/fc



Citycolor LED



Citybeam LED 24



Citybeam LED 12

RGBW/full color venues buildings
large facade IP66
bridges art installations concerts opening
efficient light theatres
shops max 168 LEDs wireless outdoor
temporary events RGB/fc

Headquarter: STUDIO DUE light s.r.l.

Str. Poggino, 100 - 01100 Viterbo (Italy)
tel. +39.0761.352520 (4 lines)
fax +39.0761.352653

STUDIO DUE UK

3 Encon Court, Owl Close
Moulton Park Industrial Estate
Northampton (England) UK - NN3 6 HZ
tel. +44.1933.650.820

STUDIO DUE Far East LTD

Unit 8, 4/F, Harbour Centre Tower II, 8 Hok Cheung St,
Hungghom, Kowloon (Hong Kong)
tel. +852.29542141 fax +852.23302515


www.studiodue.com

emotion and creativity in light