

RDM - 6TS

DMX-512A(RDM) Signal splitter

6 ways in truss mount



The 6 ports truss mount RDM splitter RDM-6TS is designed for system distribution of DMX-512A(RDM) network. Use as easy as the normal DMX-512 splitter; plug and play with XLR 5 pin connectors.

Features

- Compatible for both DMX-512A(RDM) and DMX-512(1990)
- Truss mount housing design can easy wrap on the aluminum truss with magic tie
- Signal In/Thru (XLR 5pin) and 6 ports Signal buffered output (XLR 5 pin)
- Signal Line Out or Terminate push button for signal on going or stop
- CE / ETL/cETL and FCC marked

RDM - Remote Device Management

E1.20 (RDM) is an extension to E1.11 (DMX512-A). A key goal of this standard is to allow the use of new and legacy DMX512 receiving devices in mixed systems with new RDM equipment and to provide a straightforward path to upgrade existing DMX512 distribution systems for support of the RDM protocol. The use of RDM devices in an DMX-512A system will not compromise any DMX-512A functionality.

The physical layer requirements of RDM are based on those of DMX-512A, with additional requirements related to bidirectional communication.

DMX-512(RDM) is the DMX-512A base with RDM message report function back to the control sender with messages of manufacturer, product, model, channel numbers, defined functions status...etc.

DMX-512A(RDM) or RDM is fully compatible to DMX-512(1990) & DMX-512A



SPECIFICATION SUBMITTAL

CONSULTANT: <input type="text"/>	PROJECT NAME: <input type="text"/>	MODEL NUMBER QUANTITY: <input type="text"/> <input type="text"/> <input type="text"/> <input type="text"/> <input type="text"/> <input type="text"/>
DATE: <input type="text"/>	PROJECT NUMBER: <input type="text"/>	APPROVED BY: <input type="text"/>



Technical Specifications

Supply Voltage: AC100-240V, 50/60 Hz, 5W

Standards Compliance: RDM-6TS is CE and ETL/cETL marked



Environmental Data

Temperature: 0 to 35°C
Humidity Range: 0 to 95% Non-condensing

Mechanical Data

Connections: DMX512 Input and Thru (on one side)
6 ports of DMX-512A(RDM) output (on other side)
Weight: 1.45 kg
Dimensions: 264 x 134 x 120mm

Ordering Information

Cat No.	Description
DMX512A(RDM) Splitter	
RDM6TS	DMX512A(RDM) 6 ports splitter, truss mount

DMX512A(RDM) Splitter

RDM6TS DMX512A(RDM) 6 ports splitter, truss mount

Philips Entertainment U.S.
10911 Petal Street
Dallas, TX 75238
Tel: +1 214647 7880
Fax: +1 214647 8030

Philips Entertainment Lighting Asia Limited
Unit C, 14/F, Roxy Industry Centre
No. 41 - 49 Kwai Cheong Road
Kwai Chung, N.T. Hong Kong
Tel: +852 27969786
Fax: +852 27986546

Philips Entertainment Group Europe
Rondweg Zuid 85
Winterswijk 7102 JD Netherlands
Tel: +31 543-542343
Fax: +31 53 4500425

Philips Entertainment New Zealand
19 - 21 Kawana Street, Northcote
Auckland 0627, New Zealand
Tel: +64 9481 0100
Fax: +64 9481 0101