



**INGROUND 103S-C** is designed for in-ground or in-wall installations, with customized optics in order to create the optimum in optical performance delivering both excellent color mixing and high output. It is engineered with internal driver and individual fixture addressing to achieve the dynamic lighting control. Its IP67 rating makes it the perfect outdoor and indoor architectural wash application.

**SOURCE** Light source: 3x3 Cool white  
LED life expectancy: 50,000 Hrs  
Peak Intensity: 2500 cd (16°)

**OPTICAL SYSTEM** Optics: 16°

**CONTROL & PROGRAMMING** Control Protocols: DMX, RDM  
DMX control channels: 0-100%  
Controllable sections: 1  
Color: Cool white

**ELECTRICAL** Input Voltage: AC100-240V, 50/60Hz  
Max Power: 12 W  
Power Factor: >0.6

**CONNECTIONS** Main connections: 3m cable (input only)  
Data connection: 3m cable (input + output)

**PHYSICAL** Dimensions: 133x175.2mm (square)  
Net Weight: 2kg  
Color: Black  
Housing: Die-cast aluminum  
Over 3000KG static load-bearing  
IP Rating: IP67, IK10  
Operation temperature: - 40°C~45°C (operating) /  
- 20°C~45°C (startup)

## Dimensions

