



Rigging Materials

A full range of rigging accessories is available for any set ups using ground supported towers and structures as roof systems or installs. A selection of hardware has been selected for safety, dead hanging, rigging and guy wiring. All items meet the working load requirements and safety standards.



IAL DEN

T



Round slings



Polyester round slings are used when materials like chain, wire rope could damage the load.

- According to standard EN 1492-2
- Safety factor 7
- Label in protective cover
- Computerized stitching
- Double woven jacket
- Polyester
- Sealed per piece with CE declaration and manual

Round slings

Productcode	Capacity	Circumference
ESERO1-***Z	1000 kg. WLL	2/3/4/6 m.
ESERO2-***Z	2000 kg. WLL	2/3/4/6 m.

Fill in Circumference "***" in the productcode

Stage softsteel



Polyester round slings equipped with a steel wire rope instead of the regular polyester lining.

- For extended temperature range, max. 175°C / 347 °F
- According EN 1492-2; 13414-1 and 13414-3
- Round sling with steel wire rope instead of the normal polyester lining

Stage softsteels

Productcode	Capacity	Circumference
ESERO1-***SK	1000 kg. WLL	1/2/3 m.
ESERO2-***SK	2000 kg. WLL	1/2/3/4/5/6 m.

Fill in Circumference "***" in the productcode

Buckle strap



Lashings with Buckle

- One piece
- Black lashing
- Width 25mm.

Buckle straps

Productcode	Width	Lengths
ESG25L1-***	25 mm.	1/2/3/4/5/6/7 m.

Fill in length "***" in the productcode

Ratchet lashing



- Black lashing According EN 12195-2
- 1 or 2 part (2 part is equipped with closed double J hook)

Ratchet lashings

Ratchet 1 part

Productcode	Load capacity	Length	Width
ESR25L1-**	250 kg.	3,4,5,6,8 m.	25 mm.
ESR25Z1-**	750 kg.	3,4,5,6,8 m.	25 mm.
ESR35Z1-**	1500 kg.	3,4,5,6,8 m.	35 mm.
ESR50Z1-**	2500 kg.	3,4,5,6,8 m.	50 mm.

Ratchet 2 part

Productcode	Load capacity	Length	Width
ESR25L2-**	250 kg.	3,4,5,6,8 m.	25 mm.
ESR25Z2-**	750 kg.	3,4,5,6,8 m.	25 mm.
ESR35Z2-**	1500 kg.	3,5,8 m.	35 mm.
ESR50Z2-**	2500 kg.	3,5,8 m.	50 mm.

Fill in length "***" in the productcode

Steels



Steels are according to NEN-EN 12385-4 and colour coding is referring to the length (ARGH).

- Flexible wire rope slings (construction 6x19+FC and 6x36WS+FC)
- Available in WLL 1t (d=10mm) en 2t (d=14mm) with or without PVC tube
- Ends with thimble and clamped with a tapered talurit
- Tapered talurit with inspection eye
- 1t version with oversized thimble fit is a 3,25t bowshackle, 2t fit is a 4,75t bowshackle.

Stage softsteels

Productcode	Capacity	Working lengths
CTST1-**	1000 kg. WLL	0,5 - 6 m.
CTST2-**	2000 kg. WLL	0,5 - 6 m.

Fill in working length "***" in the productcode
Add a P behind the product code for the PVC tube version, for example: CTST1-01P

Beam clamp



A beam clamp is a simple and safe temporary anchor point. Ideal for quick attachment of loads using threaded spindle. The clamp can be installed by twisting the spindle, place it over the flange and close tightly.

- Robust construction, frame is made from solid steel plate and a galvanized spindle
- Low head room, wide flange width adjustment range, therefore ideal in many situations

Buckle straps

Productcode	Capacity	Flange width
ELBC010	1000 kg. WLL	75 - 230 mm.
ELBC020	2000 kg. WLL	75 - 230 mm.
ELBC030	3000 kg. WLL	80 - 322 mm.
ELBC050	5000 kg. WLL	90 - 322 mm.
ELBC100	10000 kg. WLL	90 - 322 mm.

Chain sets



Completely in black, both chain and components. The chain shown on the left is with a connector, the connector can also be replaced by omega links, also multiple leg chain slings are available.

The displayed sling chain contains of:

- 1 Master link
- 1 Connector
- 1 Metre chain
- 1 Clevis sling hook with latch
- 1 Shortening clutch

Grade 100 chainsets

Productcode	Capacity	Ø & Length
<i>BLP-1-06-1.0-TVKCSH-Z</i>	1400 kg. WLL	06 x 1000 mm.
<i>BLP-1-08-1.0-TVKCSH-Z</i>	2500 kg. WLL	08 x 1000 mm.
<i>BLP-1-10-1.0-TVKCSH-Z</i>	4000 kg. WLL	10 x 1000 mm.
<i>BLP-1-13-1.0-TVKCSH-Z</i>	6700 kg. WLL	13 x 1000 mm.

Grade 100 chainsets with shortening clutch

Productcode	Capacity	Ø & Length
<i>BLP-1-06-1.0-TVKCSH+Z</i>	1400 kg. WLL	06 x 1000 mm.
<i>BLP-1-08-1.0-TVKCSH+Z</i>	2500 kg. WLL	08 x 1000 mm.
<i>BLP-1-10-1.0-TVKCSH+Z</i>	4000 kg. WLL	10 x 1000 mm.
<i>BLP-1-13-1.0-TVKCSH+Z</i>	6700 kg. WLL	13 x 1000 mm.

Master link



- According to EN 1677-4 with increased load capacity
- For 1- and 2- leg chains

Master links

Productcode	Load capacity	Master link for chain for Ø	
		Ø 1 leg	Ø 2 leg
<i>BLP-MLF-13-Z</i>	2300 kg.	6 mm.	6 mm.
<i>BLP-MLF-16-Z</i>	3500 kg.	8 mm.	-
<i>BLP-MLF-18-Z</i>	5000 kg.	10 mm.	8 mm.
<i>BLP-MLF-20-Z</i>	7600 kg.	13 mm.	10 mm.

Bow Shackles Pin/Bolt



- Allowed to use for lifting purposes
- Galvanized
- All shackles are marked with: WLL, Batchcode of the manufacturer, CE mark, Mark of the manufacturer
- Safety factor 6
- Conform the NEN 13889
- Temperature range: -20° C up to + 200° C
- 2t, 3,25t and 4,75t are available in black

Bow shackles pin/bolt

Productcode	Capacity	Ø Pin	Ø Bow
JHBB01000	1000 kg. WLL	12 mm.	9 mm.
HBB02000Z	2000 kg. WLL	16 mm.	13 mm.
HBB03250Z	3250 kg. WLL	20 mm.	16 mm.
HBB04750Z	4750 kg. WLL	22 mm.	19 mm.
JHBB06500	6500 kg. WLL	27 mm.	22 mm.

Automatic self-leveling rotary laser



The right choice for users who need a 360°, one-person leveling solution right out of the box.

- Self leveling
- Robust, shock-resistant housing
- Leveling range 5 °
- Range 300 m
- Rotation speed 600 RPM

Automatic self-leveling rotary laser

Productcode	Description
RT-SLL-ST	Selfleveling rotary laser kit
RT-TP-ST	Tripod for self-leveling rotary laser

Windwarning meter



The Windwarning meter was developed for alarming preset windspeed conditions. Two alarms could be set and will be announced either optical via a red LED and an acoustic sounder

- Measures Average Windspeed
- Measures Actual Windspeed
- 4 Alarms available for low and high wind speeds
- Optical and acoustic alarm
- Very low power consumption, works on 2 AA batteries
- Swiss made

Windwarning meter

Productcode	Description
RT-WVVS	Windwarning meter

S.T.A.C. Chain



Special Theatrical Alloy Chain (STAC) is ideal for theatrical rigging applications where bridle adjustability is required Meets EN 818-1 & EN 818-2 standards.

- Workingload limits of 5,4t, Safety factor 4:
- Heat treated Grade 80 Alloy Steel
- Fire & Abrasion resistant
- After production each link tested
- Easy Identification: embossed with STAC and CM
- Link accepts up to 3/4" shackle.

S.T.A.C. Chains

Productcode	Load capacity	Length
S-695550D250	5400 kg.	76 m./250 ft. drum
S-695550D500	5400 kg.	152 m./500 ft. drum
S-STAC-0.95	5400 kg.	0,95 m. (10 links)
S-STAC-1.52	5400 kg.	1,52 m. (16 links)

Multitool



Cut from 4mm hardened steel the Multitool offers exceptional durability and versatility. It includes 14 separate tools designed around some of the most common needs in the professional rigging industry.

- 3/8", 1/2", 3/4" nut tools
- 7mm (M6) square nut tool
- 18mm (M10), 20mm (M12), 24mm (M14) nut tools
- 4mm and 6mm eyelets
- Wire stripper (x2)
- Wingnut tool
- Barndoor tool
- Bottle opener

Identification label

Productcode	Length x Width	Weight
ELMULTITOOL	180 x 80 mm	0,15 kg.

Four Way Podger Wrench



Four wrench sizes in one tool! The Wrench comes in a chrome plated finish, with a slot and D-ring adapter for attachment to standard rigger tool lanyards for safer working at height.

- 4 socket sizes: 17, 19, 21, 24mm
- 24cm short handle design
- Nickel chrome plated finish
- Pointed end handle, ideal for knocking out truss pins
- Includes D-ring for lanyard attachment

Identification label

Productcode	Length	Weight
ELWRENCH4WAY	246 mm.	0,48 kg.

Recoilless Hammer Nylon



- Recoilless Hammer with nylon caps

Clevis sling hooks

Productcode	Description
RT-HAM-40	Recoilless Hammer with nylon caps

Recoilless Hammer Combi



- Recoilless Hammer with nylon and steel cap

Shortening Clutch

Productcode	Description
RT-HAM-40C	Recoilless Hammer Combi

Layher Hammer 600gr



- Black
- With nail extractor
- Solid grip
- Weighs 600gr

Layher Hammer 600gr

Productcode	Description
RT-HAM-LH	Layher Hammer 600gr