





CPX 4120 is an outdoor LED RGBE twin head city wash. Its powerful output is able to illuminate large architectural facades or canvas, stage areas and arenas. In a rugged robust body, it features two heads that be angled and controlled separately.

SOURCE	Light source: TX high power 12 watts x 120 pcs LED life expectancy: 50,000 Hrs.	Dimensions
	Beam angle: 30° to 45° Light output: 18000 Lux @ 2m @ 12°	650
	Dimmer: Linear adjustment Color mixing: RGBW 4 dimmer curves Variable strobe Individual head control	580
	Built-in color and dynamic macros Control protocols: DMX, Master-Slave Display : 4 button LED Displayer Control channels: 4, 7, 11 CHs	670
MOVEMENT		Luminous Diagram
ELECTRICAL	Input voltage: 100-240V/50-60Hz Power consumption: 1500 watts	18,000 lux (m) 2000
CONNECTIONS	DMX connections: IP DMX In/Out cables with 3 pin screw lock connectors Power connections: IP power In/Out cable, 3 pin screw lock connectors	12° 64 64 12° Distance (m) 2 4 6 8 10
PHYSICAL	Dimensions: 650 x 580 x 670mm Net weight: 50 Kg Housing: Aluminum IP rating: 66	