





SPR X28 is a 1U 19" Rack mounted DMX Splitter with both 3pin and 5pin input and output connectors. It buffers, multiplies, isolates and protects console DMX outputs. It features 2 independent 3 pin and 5 pin DMX inputs/thru and 8 optically isolated DMX outputs (4 x 3pin and 4 x 5pin), where each can be assigned to one of the two inputs giving flexibility in data distribution.

FEATURES	Split and boost the DMX signal Power and data optically isolated DMX ports High voltage protection Selectable input source for each DMX output High brightness Power and DMX Status LED indicators Individual input selection LED indicators per output Front panel Power on/off switch	Dimensions $ \begin{array}{c} \overbrace{i}\\ i$
CONTROL &	DMX Pass-Thru	
	Input selector switches	
	Power on/off switch	173
	Power and Data LED indicators	
CONNECTIONS	Data inputs: 1 x Neutrik 5 pin XLR 1 x Neutrik 3 pin XLR Data thru: 1 x Neutrik 5 pin XLR 1 x Neutrik 3 pin XLR Data outputs: 4 x Neutrik 5 pin XLR 4 x Neutrik 3 pin XLR Power connection: powerCon input and output	
ELECTRICAL	Input Voltage: AC 88-256V 50/60 Hz	
PHYSICAL	Dimensions: 482 x 173 x 46 mm Net Weight: 1.7 Kg Color: Black	