

## ZU2200

Ultra bright professional WUXGA laser projector



- High brightness WUXGA DLP laser projector -22,000 lumens
- Extreme installation flexibility Eight interchangeable lenses
- Ultimate reliability Built-in redundancy mode
- Striking lifelike images Pure engine video processing and color matching

Ultra bright professional WUXGA laser projector



## **Specifications**

Display/image Display technology DIP Resolution WUXGA (1920x1200) Brightness 22,000 lumens ANSI brightness 18,500 Contrast ratio 2,000,000:1 Native aspect ratio 16:10 Aspect ratio - compatible 16:9,16:10 Screen size Dependent on lens Lamp info DuraCore MultiColor Laser Light source type LASER life 30,000 hours Optical Throw ratio Dependent on lens Projection distance Dependent on lens BX-CTA11, 0.65~0.75:1 BX-CTA18, 0.84~1.02:1 Lens options BX-CTA19, 1.02~1.36:1 BX-CTA20, 1.2~1.5:1 BX-CTA21, 1.5~2.0:1 BX-CTA22, 2.0~4.0:1 BX-CTA23, 4.0~7.2:1 BX-CTA27, 7.2~10.8:1 Connectivity Connections

Inputs 1 x RS232, 1 x 3D sync, 1 x Wired remote, 1 x HDBaseT, 1 x DisplayPort, 2 x HDMI, 1 x VGA, 1 x DVI-D, 1 x

3G-SDL

Outputs 1 x RS232, 1 x 3D sync, 1 x Wired remote, 1 x HDMI, 1 x 3G-SDI

Control 1 x RJ45, 1 x USB-A service, 1 x 12V trigger

General Noise level (typical) 38dB Noise level (max) 40dB Full 3D 3D IP rating TBC

OSD / display languages 12 languages: Dutch, English, French, German, Hungarian,

Italian, Japanese, Norwegian, Polish, Portuguese, Spanish

24/7 operation 360° operation

Operating: 10~85%RH, non-condensing. Storage: 5~90%RH, Operating conditions

Remote control Backlit ProAV remote

Networking LAN - display Yes LAN - wireless networking No

LAN Yes Power

AC 100-240 V @ 50/60 Hz Power supply

Power consumption (standby) 0.5W Power consumption (min) 590W Power consumption (max) 1,200W

Weight and dimensions

Dimensions (W x D x H) 25.59" x 26.85" x 11.84" Gross weight 146.61 lbs 119.05 lbs Net weight





