









 ${\sf PR300T}$  is a 600 watts COB LED Tunable white LED Profile. It delivers a constant full power output of 300W with a color temperature tunable from 2800K to 6500K. It delivers a flat and crisp field of light tweaked in temperature and tint to guarantee the best color rendering on cameras. An optional high performance Fresnel lens with barn doors can replace the profile lens offering an even Fresnel wash from the same LED engine. With a high CRI of 96, this LED Profile is the perfect fit in studios and theatres.

**SOURCE**: Light source: 600 watts COB LED (300W WW + 300W CW)

LED life expectancy: 50,000 Hrs. Color temperature: 2800K-6500K

CRI: 96, R9≥90

TLCI: 98

OPTICAL: Light output: 14,000 Lux @ 2m @ 18°

**SYSTEM**: Manual zoom

Zoom Lens Angle: 18° to 38°

Optional Fresnel Lens Adapater 25°-50° (PMMA)

Optional Iris and Gobo Holder Gobo Size: OD=58mm/ID=50mm

**KEY**: 5 Dimmer curves

FEATURES: Color mixing: Tunable white

Strobe

Video flicker free with selectable PWM

Intelligent temperature control

Silent Operation

**CONTROL &**: Control protocols: Rotary, DMX, RDM **PROGRAMMING**: Control channels: 2, 4, 5 CHs

**ELECTRICAL**: Input voltage: 100-240V/50-60Hz

**CONNECTIONS**: DMX connections: 3 pin and 5 pin XLR In/Out male and female

Power connections: PowerCon In/Out

PHYSICAL : Dimensions: 745 x 294 x 294mm

Weight: 8.7kg Housing: Plastic Color: Black IP rating: 20

Operating Temperature: -5°C/45°C

**Dimensions** 



