FLX S24 CONSOLE



The Strand FLX S24 Console is a 24 fader lighting control surface that brings the legacy and power of Strand consoles in an easy-to-use package at an affordable price. A lighting design-centric console built for the non-designer, the FLX S24 allows any user to quickly create beautiful looks in less time, and is the perfect console for schools, houses of worship, broadcast studios, and portable applications.

Built on the award-winning ZerOS software, the FLX S24 includes an intuitive, user-friendly interface with a 7" multitouch screen, four physical encoders and seven dedicated physical buttons for easy operation. The ZerOS software makes it easy to design the perfect look, with multiple color selection options and intuitive moving head fixture control. To ensure users can get the job done without getting lost, ZerOS includes an on-board Guidance tool and quick select Z button.

The Strand FLX S24 Console supports 48 fixtures and offers up to 1024 channels of DMX control connected via the two 5-pin DMX ports or Ethernet based DMX. To simplify patching and monitoring of connected luminaires, the ZerOS software includes exclusive RigSync technology, for a seamless experience with less effort.



FLX S24 CONSOLE

FEATURES AND BENEFITS

- Cost effective 24 fader console from Strand with support for 1024 channels of control – affordable lighting control from the original name in theatrical lighting.
- Award-winning ZerOS software mature, easy-to-use software you can trust.
- **Simple "three-step programming" –** select what you want, where you want to control them, and how you want them to look.
- 7" Multitouch screen easily adjust colors, moving lights, and other settings.
- 4 physical encoders and 7 dedicated buttons for go, record, delete, etc. faster and more intuitive control, particularly in a live environment.
- **Image picker for control selection -** upload a photo and select different colors in one or more spots in the image to add color variation and depth.
- Multicell fixture support control all pixels in a multiple pixel fixture as easily as single-cell fixtures without intensity conflicts. Easily apply color gradients and dynamic effects.
- Mood Boards by LEE Filters quickly select the perfect color palette for your mood.
- Onscreen Guidance tool never get lost thanks to situationally aware, but unintrusive on-screen tips and advice in English, Spanish, French, and German.
- Exclusive Z button for quick access to important tools easily perform common actions anywhere in the console.
- Two 5-Pin DMX ports and support for Ethernet protocols such as Art-Net, sACN,
 CITP, etc. versatile network and physical connectivity options
- **Up to 64 universes of DMX connectivity -** control all the fixtures in your rig and patch them however you want to organize them.
- **RigSync-** simplify commissioning and management thanks to exclusive technology that finds fixtures using RDM, automatically patches them, then continually monitors the system and adapts to changes.


LIMITED WARRANTY

Every Strand product is backed by a minimum 2-year limited warranty against manufacturing defects and workmanship. Refer to the Strand Limited Warranty Card available at www.strandlighting.com/global/support/warranty for more details.

FLX S24 CONSOLE

POWER		
Supply voltage range	100 - 240V AC; max 2A	
Frequency	50 - 60Hz	
FRONT PANEL		
Faders	24x multifunctional (channels or playbacks, with select or go buttons)	
Display	1x internal 7" multi-touch screen	
Playback	1x Master Playback with Go Button playback and master intensity	
Encoder wheels	4x embedded with select buttons	
Key functions	6x Dedicated buttons	
INPUTS / OUTPUTS		
XLR connectors	2x 5-pin for DMX and RDM	
Ethernet	RJ45 (sACN, Art-Net 4, CITP (visualization) and Remote Apps)	
USB ports	2x multipurpose for saving shows, connection of accessories, software updates)	
DVI-D monitor	not applicable	
Power supply	External	
SOFTWARE		
Control	48 fixtures using single or multiple DMX channels	
Playbacks	49x equivalent of Cue Stacks, Submasters or Chases	
Cues	10,000	
Palettes	5 x 48 (Color, Beam, Shape, Position, Effect)	
Groups	48	
PHYSICALS		
Finish	Gray	
Construction	High density and impact resistant aluminum and plastics	
ENVIRONMENT	°C	°F
Operating temperature	5-40	41-104
DIMENSIONS	mm	in
H x W x D	68 x 461 x 284	2.7 × 18.1 × 11.2
WEIGHT	kg	Ib
Net weight	4	8.8
APPROBATIONS		
Approvals / Listings	cETLus, C-Tick	

FLX S24 CONSOLE







INCLUDED ITEMS

Quick Start Guide

External power supply

PRODUCT NAME	ORDER CODE
FLX S24 Console	54108-020
Dustcover	54108-001
Rackmount kit	54108-002
Replacement PSU	54109-100

©2021 Signify Holding. All rights reserved.

All trademarks are owned by Signify Holding or their respective owners. The information provided herein is subject to change, without notice. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. Data subject to change.

Ref: 54108-020-100-00