









FR 40C is designed for short distance wash. It is a super compact, easy for setup LED Fresnel powered by 40 watts 5600K daylight LED. Featuring 25 to 90° zoom, 95 CRI, 90 R9, rotary control of dimmer. It delivers a smooth, soft and flat field of light. A barn door is included to shape the light.

SOURCE: Light source: 40 watts Cool white COB LED

Color temperature: 5600K LED life expectancy: 50,000 Hrs

OPTICAL: Manual zoom

SYSTEM: Zoom range: 25° to 90°

Light output: 14,000 Lux @ 1m @ 25°

PHOTOMETRICS: CRI (Color Rendering Index):>95; R9>90

CQS (Color Quality Scale): >96

TM-30 Rf (IES TM-30-15 Fidelity Index): >92 TM-30 Rg (IES TM-30-15 Gamut Index): >98 TLCI (Television Lighting Consistency Index): >98

KEY: 5 Dimmer curves

FEATURES: Strobe

Video flicker free

PMMA polymethyl methacrylate lens

Barn doors included

CONTROL & Control protocols: Rotary, DMX, RDM **PROGRAMMING** Control channels: 1, 2, 3, 4 CHs

ELECTRICAL Input voltage: AC100-240V/50-60Hz

: DMX Connections: 3 pin XLR In/Out male and female

CONNECTIONS Power connections: PowerCon In

PHYSICAL Dimensions: 230 x 156 x 279mm


Net weight: 1.7 Kg (barn door included)


Color: Black

Housing: Aluminum

IP rating: 20; Operating temperature: -5°C/45°C

Dimensions





Luminous Diagram

