









FR 40W is designed for short distance wash. It is a super compact, easy for setup LED Fresnel powered by 40 watts 3200K tungsten. Featuring 25 to 90° zoom, 97 CRI, 90 R9, rotary control of dimmer. It delivers a smooth, soft and flat field of light. A barn door is included to shape the light.

 $\textbf{SOURCE} \; \underline{:} \; Light \, source \\ \underline{:} \; 40 \, watts \, Warm \, white \, COB \, LED$

Colortemperature: 3200K LED life expectancy: 50,000 Hrs

OPTICAL Manual zoom

Zoom range: 25° to 90° manual
Light output: 14,000 Lux @ 1m @ 25°

PHOTOMETRICS : CRI (Color Rendering Index): >95; R9>90

CQS (Color Quality Scale): >96

TM-30 Rf (IES TM-30-15 Fidelity Index): >92 TM-30 Rg (IES TM-30-15 Gamut Index): >98 TLCI (Television Lighting Consistency Index): >98

KEY: 5 Dimmer curves

FEATURES Strobe

Video flicker free

PMMA polymethyl methacrylate lens

Barn doors included

CONTROL &: Control protocols: Rotary, DMX, RDM **PROGRAMMING**: Control channels: 1, 2, 3, 4 CHs

ELECTRICAL: Input voltage: AC100-240V/50-60Hz

CONNECTIONS: DMX Connections: 3 pin XLR In/Out male and female


Power connections: PowerCon In


PHYSICAL : Dimensions: 230 x 156 x 279mm

Net weight: 1.7 Kg (barn door included) Color: Black; Housing: Aluminum

IP Rating: 20; Operating temperature: -5°C/45°C

Dimensions





Luminous Diagram

