

[Click to Print This Page](#)



# E-VISION 9100 WU DIGITAL PROJECTOR

THE VISIONARIES CHOICE




## E-Vision 9100 WU

**8,600 ISO / 7,700 ANSI Lumens | Contrast Ratio: 20,000:1 (dynamic) | Part Number: 120-976**

### Key Specifications:

<b>Colour System:</b>	Laser Phosphor
<b>Display Type:</b>	1 x 0.67" DarkChip™ DMD™
<b>DMD Specification:</b>	1920 x 1200 pixels native display. Fast transit pixels for smooth greyscale and improved contrast.
<b>Aspect Ratio:</b>	16x10
<b>Fill Factor</b>	87%
<b>Key Features:</b>	<p><b>Video &amp; Graphics Processing</b></p> <ul style="list-style-type: none"><li>• HDMI 2.0 for Side by Side, Frame Packing &amp; Top Bottom 3D Formats</li><li>• Dual flash processing can be used to multiply the displayed frame rate for 3D sources</li><li>• Triple Flash Processing for 144Hz 3D display</li><li>• Synchronisation of active glasses</li><li>• 24p and 1080p native display</li><li>• Sealed light engine</li><li>• DICOM Simulation Mode</li><li>• HDR Support</li><li>• Powerful 7 point colour correction for accurate colour matching</li></ul> <p><b>Geometry Correction</b></p> <ul style="list-style-type: none"><li>• Cornerstone, Vertical &amp; Horizontal Keystone</li><li>• Selectable Aspect Ratios</li><li>• Digital Zoom</li></ul>

	<p><b>HDBaseT® Interface</b></p> <ul style="list-style-type: none"> <li>• Built in support for transmission of uncompressed High Definition Video over standard CAT5e/6 LAN cable</li> <li>• Allows projector to be placed up to 100m from source with low cost cabling</li> <li>• Projector Control via HDBaseT</li> </ul>																																																																		
<b>Source Compatibility</b>	<p>HDMI including Deep Color™ processing.  Graphics standards support up to 3840 x 2160 (4K-UHD) &amp; 4096 x 2160 (full 4K) resolution via HDMI  Graphics standards up to native 1920 x 1200 resolution @ 60Hz via DVI-D, HDBaseT or VGA  Component Video (SD and HD) via RGBHV.</p>																																																																		
<b>Inputs/Outputs</b>	<table border="1"> <thead> <tr> <th colspan="3">Video &amp; Computer</th> </tr> <tr> <th>Type</th> <th>Connector</th> <th>Qty</th> </tr> </thead> <tbody> <tr> <td>HDMI 2.0</td> <td>HDMI</td> <td>2</td> </tr> <tr> <td>DVI-D 1.0</td> <td>DVI</td> <td>1</td> </tr> <tr> <td>VGA / Analog RGB</td> <td>15-pin D-Sub</td> <td>1</td> </tr> <tr> <td>Component Video</td> <td>5 x BNC</td> <td>5</td> </tr> <tr> <td>HDBaseT</td> <td>RJ45</td> <td>1</td> </tr> <tr> <td>Video Out: VGA</td> <td>15-pin D-Sub</td> <td>1</td> </tr> <tr> <td>Audio In: Stereo</td> <td>3.5mm Jack</td> <td>1</td> </tr> <tr> <td>Audio Out: Stereo</td> <td>RCA</td> <td>2</td> </tr> </tbody> </table> <table border="1"> <thead> <tr> <th colspan="3">Communication &amp; Control</th> </tr> <tr> <th>Type</th> <th>Connector</th> <th>Qty</th> </tr> </thead> <tbody> <tr> <td>3D Sync Out</td> <td>Mini DIN</td> <td>1</td> </tr> <tr> <td>3D Sync In</td> <td>BNC</td> <td>1</td> </tr> <tr> <td>LAN</td> <td>RJ45</td> <td>1</td> </tr> <tr> <td>Serial In (RS232)</td> <td>9-pin D-Sub</td> <td>1</td> </tr> <tr> <td>Serial Out (RS232)</td> <td>9-pin D-Sub</td> <td>1</td> </tr> <tr> <td>Wired Remote In</td> <td>3.5mm Stereo Jack</td> <td>1</td> </tr> <tr> <td>Wired Remote Out</td> <td>3.5mm Stereo Jack</td> <td>1</td> </tr> <tr> <td>12V Trigger</td> <td>3.5mm Stereo Jack</td> <td>1</td> </tr> <tr> <td>USB (power only)</td> <td>USB Type A 5V / 2A</td> <td>1</td> </tr> <tr> <td>USB (Service)</td> <td>USB Type B</td> <td>1</td> </tr> </tbody> </table>	Video & Computer			Type	Connector	Qty	HDMI 2.0	HDMI	2	DVI-D 1.0	DVI	1	VGA / Analog RGB	15-pin D-Sub	1	Component Video	5 x BNC	5	HDBaseT	RJ45	1	Video Out: VGA	15-pin D-Sub	1	Audio In: Stereo	3.5mm Jack	1	Audio Out: Stereo	RCA	2	Communication & Control			Type	Connector	Qty	3D Sync Out	Mini DIN	1	3D Sync In	BNC	1	LAN	RJ45	1	Serial In (RS232)	9-pin D-Sub	1	Serial Out (RS232)	9-pin D-Sub	1	Wired Remote In	3.5mm Stereo Jack	1	Wired Remote Out	3.5mm Stereo Jack	1	12V Trigger	3.5mm Stereo Jack	1	USB (power only)	USB Type A 5V / 2A	1	USB (Service)	USB Type B	1
Video & Computer																																																																			
Type	Connector	Qty																																																																	
HDMI 2.0	HDMI	2																																																																	
DVI-D 1.0	DVI	1																																																																	
VGA / Analog RGB	15-pin D-Sub	1																																																																	
Component Video	5 x BNC	5																																																																	
HDBaseT	RJ45	1																																																																	
Video Out: VGA	15-pin D-Sub	1																																																																	
Audio In: Stereo	3.5mm Jack	1																																																																	
Audio Out: Stereo	RCA	2																																																																	
Communication & Control																																																																			
Type	Connector	Qty																																																																	
3D Sync Out	Mini DIN	1																																																																	
3D Sync In	BNC	1																																																																	
LAN	RJ45	1																																																																	
Serial In (RS232)	9-pin D-Sub	1																																																																	
Serial Out (RS232)	9-pin D-Sub	1																																																																	
Wired Remote In	3.5mm Stereo Jack	1																																																																	
Wired Remote Out	3.5mm Stereo Jack	1																																																																	
12V Trigger	3.5mm Stereo Jack	1																																																																	
USB (power only)	USB Type A 5V / 2A	1																																																																	
USB (Service)	USB Type B	1																																																																	
<b>3D Formats Supported</b>	<p>Frame Packing  Side By Side (half)  Top and Bottom  Frame Sequential</p>																																																																		
<b>HDTV Formats Supported</b>	1080p (24Hz, 25Hz, 30Hz, 50Hz, 60Hz), 1080i (50Hz, 60Hz), 720p (50, 60Hz)																																																																		
<b>Computer Compatibility</b>	<p>Up to 1920 x 1200 via DVI-D, HDBaseT, VGA  Up to 4096 x 2160 via HDMI</p>																																																																		
<b>Bandwidth</b>	<p>165 MHz on analog RGB  498 Megapixels per second on HDMI</p>																																																																		
<b>Remote Control</b>	<p>IR remote control, wireless and wired.  On-Board keypad</p>																																																																		
<b>Automation Control</b>	<p>Crestron RoomView® Connected  PJLink  LAN  RS232</p>																																																																		

	AMX-SSDP Extron																																				
<b>Colour Temperature</b>	User Selectable																																				
<b>Operation</b>																																					
<b>illumination Type</b>	Laser Light Source																																				
<b>Typical illumination Life</b>	20,000 hours																																				
<b>Lenses</b>	<table border="1"> <thead> <tr> <th>Lens</th> <th>Part No.</th> <th>Optimised Focus Range*</th> <th>Lens Shift (Frame)</th> </tr> </thead> <tbody> <tr> <td>0.38 :1 fixed</td> <td>117-341</td> <td>0.68m - 2.44m</td> <td>Depends on image size, see Installation Guide.</td> </tr> <tr> <td>0.75 - 0.93 :1 zoom</td> <td>115-339</td> <td>1.02m - 12.7m</td> <td>Vert: 0.55 (U) 0.15 (D) frame, Hor: 0.05(L) 0.05 (R) frame</td> </tr> <tr> <td>0.76 :1 fixed</td> <td>112-499</td> <td>0.81m - 5.08m</td> <td>none</td> </tr> <tr> <td>1.25 - 1.79 :1 zoom</td> <td>112-500</td> <td>1.33m - 11.73m</td> <td>Vert: 0.55 (U) 0.15 (D) frame, Hor: 0.05(L) 0.05 (R) frame</td> </tr> <tr> <td>1.73 - 2.27 :1 zoom</td> <td>112-501</td> <td>1.83m - 14.9m</td> <td>Vert: 0.55 (U) 0.15 (D) frame, Hor: 0.05(L) 0.05 (R) frame</td> </tr> <tr> <td>2.22 - 3.67 :1 zoom</td> <td>112-502</td> <td>2.36m - 24.2m</td> <td>Vert: 0.55 (U) 0.15 (D) frame, Hor: 0.05(L) 0.05 (R) frame</td> </tr> <tr> <td>3.58 - 5.38 :1 zoom</td> <td>112-503</td> <td>3.8m - 35.35m</td> <td>Vert: 0.55 (U) 0.15 (D) frame, Hor: 0.05(L) 0.05 (R) frame</td> </tr> <tr> <td>5.31 - 8.26 :1 zoom</td> <td>112-504</td> <td>5.59m - 54.8m</td> <td>Vert: 0.55 (U) 0.15 (D) frame, Hor: 0.05(L) 0.05 (R) frame</td> </tr> </tbody> </table> <p>* Lens focal ranges above are the optimised distances but are likely to focus further, please contact your RSM for more details. Lens ratio tolerances: E-Vision Series: +/-3%. HighLite Series: +/- 5%. M-Vision Series: +/- 2%. Titan Series: +/-2%, INSIGHT Series: +/-2%,</p>	Lens	Part No.	Optimised Focus Range*	Lens Shift (Frame)	0.38 :1 fixed	117-341	0.68m - 2.44m	Depends on image size, see Installation Guide.	0.75 - 0.93 :1 zoom	115-339	1.02m - 12.7m	Vert: 0.55 (U) 0.15 (D) frame, Hor: 0.05(L) 0.05 (R) frame	0.76 :1 fixed	112-499	0.81m - 5.08m	none	1.25 - 1.79 :1 zoom	112-500	1.33m - 11.73m	Vert: 0.55 (U) 0.15 (D) frame, Hor: 0.05(L) 0.05 (R) frame	1.73 - 2.27 :1 zoom	112-501	1.83m - 14.9m	Vert: 0.55 (U) 0.15 (D) frame, Hor: 0.05(L) 0.05 (R) frame	2.22 - 3.67 :1 zoom	112-502	2.36m - 24.2m	Vert: 0.55 (U) 0.15 (D) frame, Hor: 0.05(L) 0.05 (R) frame	3.58 - 5.38 :1 zoom	112-503	3.8m - 35.35m	Vert: 0.55 (U) 0.15 (D) frame, Hor: 0.05(L) 0.05 (R) frame	5.31 - 8.26 :1 zoom	112-504	5.59m - 54.8m	Vert: 0.55 (U) 0.15 (D) frame, Hor: 0.05(L) 0.05 (R) frame
Lens	Part No.	Optimised Focus Range*	Lens Shift (Frame)																																		
0.38 :1 fixed	117-341	0.68m - 2.44m	Depends on image size, see Installation Guide.																																		
0.75 - 0.93 :1 zoom	115-339	1.02m - 12.7m	Vert: 0.55 (U) 0.15 (D) frame, Hor: 0.05(L) 0.05 (R) frame																																		
0.76 :1 fixed	112-499	0.81m - 5.08m	none																																		
1.25 - 1.79 :1 zoom	112-500	1.33m - 11.73m	Vert: 0.55 (U) 0.15 (D) frame, Hor: 0.05(L) 0.05 (R) frame																																		
1.73 - 2.27 :1 zoom	112-501	1.83m - 14.9m	Vert: 0.55 (U) 0.15 (D) frame, Hor: 0.05(L) 0.05 (R) frame																																		
2.22 - 3.67 :1 zoom	112-502	2.36m - 24.2m	Vert: 0.55 (U) 0.15 (D) frame, Hor: 0.05(L) 0.05 (R) frame																																		
3.58 - 5.38 :1 zoom	112-503	3.8m - 35.35m	Vert: 0.55 (U) 0.15 (D) frame, Hor: 0.05(L) 0.05 (R) frame																																		
5.31 - 8.26 :1 zoom	112-504	5.59m - 54.8m	Vert: 0.55 (U) 0.15 (D) frame, Hor: 0.05(L) 0.05 (R) frame																																		
<b>Lens Mount</b>	Motorised and programmable shift, zoom and focus. Intelligent Lens Memory with 8 user-definable preset positions (except UST lens).																																				
<b>Mechanical Mounting</b>	Front/Rear Table Front/Rear Ceiling Adjustable Front/Rear Feet																																				
<b>Orientation</b>	<b>Table Top or Inverted:</b> Yes <b>Pointing Up:</b> Yes <b>Pointing Down:</b> Yes <b>Roll (Portrait):</b> Yes																																				
<b>Power Requirements</b>	100-240VAC 50/60Hz single phase																																				
<b>Power Consumption</b>	775W Typical 240VAC																																				

	792W Typical 110VAC	
<b>Thermal Dissipation</b>	2704 BTU/Hour 110V Normal Mode 2579 BTU/Hour 240V Normal Mode	
<b>Fan Noise</b>	Typical 38dBA	
<b>Operating/Storage Temperature:</b>	Operating: 0 to 40C (32 to 104F) >35C switches to Eco Mode Storage: -20 to 60C (-4 to 140F)	
<b>Operating Humidity</b>	10 to 85% non-condensing	
<b>Weight</b>	27.5 kg / 60.6 lbs	
<b>Dimensions</b>	L: 59.83cm W: 50cm H: 21.85cm L: 23.55 in W: 19.68 in H: 8.6 inch	
<b>Safety &amp; EMC Regulations</b>	CE, FCC Class B, UL, CCC, CB, RoHS, RCM, CU	
<b>Accessories</b>	Accessory	Part No.
	Infrared Remote (replacement)	120-978
	<i>*Dimensions included for reference only and are subject to change. Please download the full set of CAD files for this display for more accurate information.</i>	
<b>Downloads</b>	<a href="#">PDF CAD Drawings</a> <a href="#">AUTOCAD Drawings</a> <a href="#">STEP / IGS Drawings</a> <a href="#">Lens CAD Drawings</a>	
<b>User Guide</b>	<a href="#">User Guides</a> <a href="#">User Guides (German)</a> <a href="#">User Guides (French)</a> <a href="#">Laser Risk Group Document</a> <a href="#">Important Information</a> <a href="#">Important Information (German)</a> <a href="#">Important Information (French)</a> <a href="#">Control Protocol</a> <a href="#">Ultra Short Throw Lens</a> <a href="#">Ultra Short Throw Lens Installation Guide</a>	





Unit 3, Aniseed Park, Broadgate,

Oldham, UK OL9 9XA



T: +44 (0)161 947 3300



[www.digitalprojection.com](http://www.digitalprojection.com)



**DIGITAL PROJECTION, INC**



55 Chastain Road, Suite 115 Kennesaw, GA.

30144



T: 770.420.1350 | F: 770.420.1360



[www.digitalprojection.com](http://www.digitalprojection.com)



**DIGITAL PROJECTION, CHINA**



Rm A2301, Shaoyaoju 101 North Lane, Shi Ao

International Center, Chaoyang District, Beijing 100029,  
PR China



T: +86.10.58239771 | F: +86 10 58239770

**DIGITAL**  **PROJECTION**

Specifications subject to change without notice.  
©2024 Digital Projection. DLP®, Digital Light  
Processing™ and DMD are trademarks of Texas  
Instruments, Inc

A brand of  **DELTA**