



## Power Strip XO CCV5RD-6T1-2C (EU)

Power Strip Xtreme Outdoor. 1xC EE16A IN - 6x powerCON® TRUE1® TOP OUT & 1x CEE16A OUT

Power Strip Xtreme Outdoor (XO) is a compact distribution solution for mobile outdoor applications. Rugged EASYLEN® housing is ideally suited for outdoor usage and demanding applications under harsh conditions. 1x CEE16A In and up to 6x powerCON® TRUE1® TOP Out & 1x CEE16A Out.

## Features & Benefits

- ✓ Extreme robust and safe EASYLEN® housing with leather grain texture
- ✓ Mains receptacles CEE16A IN & daisy chaining and highly reliable NEUTRIK® powerCON® TRUE1® TOP OUT
- ✓ Flame retardant (UL94-V2) and non-conductive housing material
- ✓ High outdoor protection (IP65, IK, ..)
- ✓ Light weight, compact and stackable housing design
- ✓ Versatile mounting options

## Applications and markets

- ✓ Main markets: Professional video walls, event lighting, pro-audio
- ✓ Mobile application: Festivals, live events
- ✓ Semi-permanent applications: Theaters, studios

## Ordering Information

| Article name  | Details                                                             |
|---------------|---------------------------------------------------------------------|
| CCV5RD-6T1-2C | IN: 1xCEE16A In & daisy chaining - OUT: 6x powerCON® TRUE1® TOP Out |

## Technical Information

| Product        |                         |
|----------------|-------------------------|
| Input device   | 1xCEE16-5               |
| Output device  | 6x powerCON® TRUE1® TOP |
| Daisy chaining | 1x CEE16-5              |

| Electrical                            |                      |
|---------------------------------------|----------------------|
| Contact resistance / protection class | Protection class II  |
| Dielectric strength                   | 0,5 kV / mm          |
| Rated voltage                         | 400V AC              |
| Rated Current                         | 16A                  |
| Number of electrical contacts         | 4 + PE               |
| Phases                                | multi-phase (3+N+PE) |

## Mechanical

|                         |                                                                    |
|-------------------------|--------------------------------------------------------------------|
| Dimensions              | 528.6 x 92 x 117.2 mm                                              |
| Conductor cross section | 2,5 mm <sup>2</sup>                                                |
| Weight                  | 2.1 kg                                                             |
| Mounting options        | Truss clip, truss clamp, mounting wholes for pegging or suspension |

## Material

|         |         |
|---------|---------|
| Housing | Easylen |
| Color   | black   |

## Environmental

|                         |                  |
|-------------------------|------------------|
| Standards compatibility | UL94-V2          |
| Protection class        | IP65             |
| Temperature range       | -25 °C bis +40°C |